



Model	ASL 75 CXS NA	ASL 65 VXS NA	AS 65 VXS NA
<b>Product Line</b>	condenser dryer	vented dryer	vented dryer
<b>Color</b>	platinum	platinum	platinum
<b>Performances</b>			
Bi-directional rotation	▪	▪	▪
Removable filter	▪	▪	▪
Maximum drying load	16 lbs / 7.5 kgs	15 lbs / 6.5 kgs	15 lbs / 6.5 kgs
Alarm at end of cycle	▪	▪	▪
Controls	electronic	electronic	electromechanic
Approval	UL / CUL	UL / CUL	UL / CUL
Time to end		▪	
<b>Primary Functions</b>			
Sensor drying	Cotton / Permanent Press	Cotton / Permanent Press	
Automatic drying			Heavy load, Light load
Timed drying	up to 160 min	up to 120 min	up to 120 min
Fabric care		Delicates / Wool	
<b>Additional Options</b>			
Air Fluff	▪	▪	▪
Easy Iron	▪	▪	▪
Time Delay	up to 12 hrs	up to 18 hrs	
Pre crease care	▪	▪	
Post crease care	▪	▪	
High Heat / Low Heat	▪	▪	▪
<b>Dimensions</b>			
Product only (HxWxD)	850mm x 595mm x 584mm 33.47" x 23.43" x 23.00"	850mm x 595mm x 550mm 33.47" x 23.43" x 21.66"	850mm x 595mm x 550mm 33.47" x 23.43" x 21.66"
Product with packaging (HxWxD)	890mm x 638mm x 670mm 35.04" x 25.12" x 26.38"	890mm x 638mm x 610 mm 35.04" x 25.12" x 24.02"	890mm x 638mm x 610 mm 35.04" x 25.12" x 24.02"
Venting hole		bottom left rear	bottom left rear
Door opening	17"	13"	13"
<b>Weight</b>			
Product only	70.6 lbs / 32.0 kg	67.3 lbs / 30.5 kg	67.3 lbs / 30.5 kg
Product with packaging	81.6 lbs / 37.0 kg	70.6 lbs / 32.0 kg	70.6 lbs / 32.0 kg
<b>Technical Data</b>			
Voltage / Frequency	208-240 volts / 60 hz	208-240 volts / 60 hz	208-240 volts / 60 hz
Amperage / Wire	30 Amps / 4 prong plug	30 Amps / 4 prong plug	30 Amps / 4 prong plug
Cable length	6 ft. / 1.8 mts	6 ft. / 1.8 mts	6 ft. / 1.8 mts
Maximum absorbed power	2100 - 2750 W	2000 - 2600 W	2000 - 2600 W
Tub & Drum	Stainless Steel	Stainless Steel	Stainless Steel
Volume	3.96 cft / 112 lt	3.53 cft / 100 lt	3.53 cft / 100 lt
Adjustable feet	▪	▪	▪
<b>Accessories</b>			
Instruction Manual	English, Spanish, French	English, Spanish, French	English, Spanish, French
Stacking Kit	included	included	included
Adaptor for ventilation kit	included	included	included

(\*) Certain limitation apply, see manufacturers limited warranty for details  
 Ariston reserves the right to bring changes to the products without notice.  
 UL and CUL listed



For planning purposes only,  
 for details see care & use manual  
 Stacked installation Height 67"